

AK BEND APK 30 (1125-840456)



Control type
konventionell

Construction year
2021

Machine no.
1125-840456

Make
AK BEND

Location
Ahaus

- ** Exhibition machine from 2021
- ** with only approx. 2x operating hours
- ** Condition as NEW
- ** Special price on request

Equipment:

- robust electro-motorized ring/profile bending machine
- horizontal and vertical work possible
- * Machine head can be folded 90°
- 1x freely movable foot switch
- segmented standard rollers (divided)
- 2x motor-driven rollers
- manual delivery of the top roller
- analog position display of the top rollers (scale)
- manually adjustable side/straightening rollers
- CE mark / declaration of conformity
- Operating instructions in German

Machine attributes




L-beam:	40 x 5.0 (d 500) mm
I - beam section - flat steel:	80 x 15 (d 700) mm
I-beam section - upend:	50 x 10 (d 800) mm
round material:	30.0 (d 700) mm
bar material dia. max.:	60 x 2 (d 1200) mm
square material:	50 x 30 x 3 mm
range L-W-H:	670 x 530 x 1350 mm
weight:	185 kg
total power requirement:	0.75 kW

Machine images





© A + B Werkzeuge Maschinen Handels GmbH

TECHNICAL SPECIFICATIONS TEKNİK BİLGİLER		APK 35 SIZE AND DIAMETER ÖLÇÜLER VE ÇAP		APK 30 SIZE AND DIAMETER ÖLÇÜLER VE ÇAP		ROLLS VALS TOPLARI
		mm	min ø	mm	min ø	
1	 Angle leg out Köşebent dışı	50x5	850	40x5	400	AD
2	 Angle leg in Köşebent içi	50x5	1200	40x5	500	AD
3	 T section leg out T profil dışı	50	650	50x5	800	A
4	 T section leg in T profil içi	50	900	50	850	A
5	 T section leg side T profil yana	50	750	50	800	A
6	 Plate hard way Lama zoruna	60x10 50x12	800 800	50x10	800	A
7	 Plate easy way Lama kolayına	120x15	750	80x15	700	A
8	 Square / Kare	35x35 20x20	1200 400	30x30	700	A
9	 Round / Yuvarlak	Ø35	800	Ø50	700	B1*
10	 Tube / Boru	Ø70x2	1200	Ø90x2	1200	B1*
11	 Tube-Pipe/ Boru	Ø33,7x2,65	320	Ø48,3x3,2	900	B1*
12	 Rectangle tube Dikdörtgen Profil	50x40x3		50x30x3		B2*
13	 Square tube Kare Profil	60x60x3		40x40x3		B3*
14	 Channel easy way legs out U profil kolayına dışına	UNP60	550	UNP50	400	AD
15	 Channel easy way legs in U profil kolayına içine	UNP60	700	UNP50	500	AD
Power / Motor Gücü kW		1,5		0,75		
Rolls ø / Vals Topları ø mm		155		137/132		
Shaft ø / Mil ø mm		50/50		35/30		
Bending Speed / Bükme Hızı		43 m/min.		21 m/min.		
Weight / Ağırlık kg.		320		190		
WxLxH / GxÜxY mm.		730x330x1500		670x330x1350		