

ALMI AL 12 U (1125-8390101)

© A + B Werkzeuge Maschinen Handels GmbH



Control type
konventionell

Machine no.
1125-8390101

Make
ALMI

Location
manufactures plant

The AL1-2U electric pipe notcher is started at the push of a button, and the pipe notcher is driven continuously. This means you can continually work on new parts without having to switch the machine on again each time.

With the electrically driven AL1-2U pipe notcher you can notch pipe outer diameters of \varnothing 26.9 (3/4?), \varnothing 33.7 (1?), \varnothing 42.4 (1 1/4"), \varnothing 48.3 (1 1/2"), \varnothing 60.3 (2?).

This pipe notcher is also suitable for notching a zinc outlet in round and rectangular metal pipes. You can notch pipe outer diameters of \varnothing 20.0 -60.3.

Do you often notch pipes? Then the electrically driven pipe notcher AL1-2U with the 2.2 kW electric motor is just the thing for you. The motor forms a unit with the special eccentric shaft that drives the notching tool. The motor is also equipped with an on/off switch with 0-voltage protection and a protective cap.

Equipment:

- electro-motor pipe notching machine

- including notching station for zinc run-out notches
- for pipes 27.9 - 34.8 - 42.8 - 49.0 and 61.0 mm
- operating instructions

Machine attributes

plate thickness:	max. 5.0 mm
tube diameter:	27.9 - 61.0 mm
motor:	400 Volt
total power requirement:	2.2 kW
weight of the machine ca.:	93.0 kg.

Machine images



