

ALZMETALL ALZSTAR 40 iTRONIC - V (1125-3100024)



Control type
konventionell

Construction year
2021

Machine no.
1125-3100024

Make
ALZMETALL

Location
49779 Niederlangen

- 7" TFT LCD display with touch function:
 - * Manual input of spindle speed setpoint
 - * Speed display actual value
 - * Integrated drilling depth display with touch zero point transfer
 - * Virtual drilling depth scale in the display
 - * Service information
 - * Selectable user language: DE/EN/FR/ES/IT/NL/RU
- Infinitely variable speed setting by means of an adjusting lever
- Spindle protection with electrical fuse
- Three separate buttons for clockwise rotation - counterclockwise rotation - stop
- Mushroom pushbutton (locking) for EMERGENCY STOP
- Main switch, lockable
- Right and left rotation by contactor control
- Control voltage 24 volts, protection class IP54
- Feed overload protection
- Machine oil first fill; Oil bottle, loose delivery

- Paint finish: DD structure paint signal white RAL 9003, Pantone 7545c, black

Machine attributes

bore capacity in steel (diameter):	40 mm
throat:	293 mm
bore stroke:	120 mm
spindle taper MT:	3
column diameter:	115 mm
table surface area:	514 x 360 mm
spindle turning speed - stepless:	160 - 2250 U/min
total power requirement:	1,45 / 1,90 kW
weight of the machine ca.:	285 kg
dimensions of the machine ca.:	H: 1840 mm

Machine images



