

BERNARDO COMPACT 400 - ES 12 V (1125-8203165)



Control type
konventionell

Machine no.
1125-8203165

Make
BERNARDO

Location
48683 Ahaus

Equipment:

- 3-axis digital display ES-12 V with LCD display
- 3-jaw chuck PS3-200 mm / D5
- Clamping disk 320 mm
- Fixed steady rest - passage diameter max. 130 mm
- Follow-on steady rest - passage diameter max. 100 mm
- Coolant system
- Quick-change tool holder with 4 inserts
- Protective device for quick-change tool holder
- Micrometer longitudinal stop
- Slip clutch
- Motor with magnetic brake in accordance with CE standard
- Initial filling with Shell Tellus 46
- Extendable chip tray
- LED machine light
- Change gears
- Reduction sleeve

- 2 centering points
- Chip rear wall
- Operating tool

Machine attributes

turning length:	850 mm
turning diameter:	400 mm
swing diameter over bed slide:	245 mm
spindle bore:	52.0 mm
turning speeds:	45 - 1800 U/min
bed width:	260 mm
spindle taper:	DIN 55029 D 1-5
taper in tailstock:	3 MK
quill travel:	120 mm
total power requirement:	3.0 / 4.5 kW
weight of the machine ca.:	1255 kg
range L-W-H:	1900 x 1000 x 1610 mm

Machine images





