

BERNARDO GB 50 HS (1125-8104218)



Control type
konventionell

Machine no.
1125-8104218

Make
BERNARDO

Location
Ahaus

Scope of delivery

- Keyed drill chuck 1 - 13 mm / B 16
- Drill chuck arbor MK 4 / B 16
- Reducing sleeve MK 4 / 3, MK 4 / 2
- Motorized table stroke
- Coolant device
- Electromagnetic spindle feed
- Thread cutting device
- Automatic tool ejector
- LED machine light
- Initial filling with Shell Tellus 46
- Digital speed display
- Digital drilling depth display
- Height-adjustable protective cover

Machine attributes

bore capacity in steel (diameter):	50.0 mm
throat:	370 mm
bore stroke:	250 mm
morse taper:	4 MK
table::	600 x 500 mm
threading:	M 42 Stahl
turning speeds:	40 - 2100 U/min
feed:	0.1 - 0.4 mm/U
column diameter:	200 mm
distance spindle /table:	max. 600 mm
distance spindle/base plate:	max. 1190 mm
total power requirement:	2.2 / 2.8 kW
weight:	670 kg
range L-W-H:	1020 x 750 x 2340 mm

Machine images

© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



MA 7-20 (Stützbohle) (Maschinen) (Heinz Sanders GmbH)

