Papenburg
Heinz Sanders GmbH
Friederikenstraße 100
26871 Papenburg
info@heinz-sanders.de

Niederlangen
Heinz Sanders GmbH
Fresenburger Weg 4
49779 Niederlangen
maschinen@heinz-sanders.de

Spelle
Heinz Sanders GmbH
Robert-Bosch-Straße 9
48480 Spelle
spelle@heinz-sanders.de

BERNARDO SB 40 Profi (1125-8100277)

Control type
konventionell

Construction year
2024

Machine no.
1125-8100277

Make
BERNARDO

Location
48683 Ahaus

characteristics
- Vario drive for precise setting of the speed
- Quill infeed either by hand or by mechanical feed
- Easy tool change thanks to automatic tool ejector
- Set speed can be read quickly and easily using the digital display
- Solid, swiveling gray cast iron table with T-slots and coolant channel
- The coolant system and lighting are included in the scope of delivery
- Adjustable drilling depth stop, drilling depth can be read off using a scale
- Right-left rotation device for thread cutting

scope of delivery
- Drill chuck arbor MK 4 / B 16
- coolant device
- Digital speed display
- Keyless chuck 1 - 16 mm / B 16
- Reducing sleeve MK 4/3, MK 4/2, MK 3/1
- LED machine light
- Automatic tool ejector
- Height-adjustable protective cover

Machine attributes

bore capacity in steel (diameter):	40.0 mm
throat:	320 mm
bore stroke:	160 mm
morse taper:	4 MK
table::	505 x 425 mm
swivelling +/-:	50 Grad
T-slots:	14.0 mm
turning speeds:	90 - 1,455 U/min
quill feed:	0.1/0.2/0.3 mm/U
column diameter:	120 mm
total power requirement:	1.0 / 1.5 kW
weight of the machine ca.:	380 kg.
range L-W-H:	500 x 930 x 1870 mm

Machine images

© A + B Werkzeuge Maschinen Handels GmbH

© A + B Werkzeuge Maschinen Handels GmbH

Papenburg
Heinz Sanders GmbH
Friederikenstraße 100
26871 Papenburg
info@heinz-sanders.de

Niederlangen
Heinz Sanders GmbH
Fresenburger Weg 4
49779 Niederlangen
maschinen@heinz-sanders.de

Spelle
Heinz Sanders GmbH
Robert-Bosch-Straße 9
48480 Spelle
spelle@heinz-sanders.de

© A + B Werkzeuge Maschinen Handels GmbH

© A + B Werkzeuge Maschinen Handels GmbH