

BERNARDO TM 24 BLO / R 1200 (1125-8100034)

© A + B Werkzeuge Maschinen Handels GmbH



Control type
konventionell

Machine no.
1125-8100034

Make
BERNARDO

Location
48683 Ahaus

- with micro spray system for constant cooling & minimal Cooling lubricant consumption
- Includes blow-out device to remove chips, ensuring optimal visibility on the borehole
- Includes quick-change chuck for using taps for Through and blind holes
- Swivel motor unit for thread cutting at any desired angle between 0° and 90°
- Higher accuracy compared to manual thread cutting, thread is guaranteed right angle (90°)
- high productivity, significant time savings compared to manual Threading
- Quick-change chuck with integrated slip clutch prevents breaking of the tap
- Includes large radius swivel arm for easy positioning tap on the workpiece
- For thread cutting in steel, stainless steel, aluminum and non-ferrous metals

scope of delivery

- Operation via touchscreen
- Digital drilling depth display
- Micro spray system
- Blow-out device
- Quick change mount
- Quick-change chuck according to DIN
- Electric motor
- 90° angle adjustment
- Mounting flange

**Special accessories included:

- BERNARDO base frame 900 x 600 mm (Art. No.: 01-14390)
- Mounts: DIN 376: M5-6 / M8 / M10 / M12 / M14 / M16 / M18 / M20 / M22-24

Machine attributes

thread dia.:	M5 - M24
turning speeds:	70 - 200 U/min
working area:	max. 1200 R
angle adjustable from - to:	0 - 90 Grad
voltage:	230 V
engine output:	1200 W
weight:	65,0 kg

Machine images

© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH

© A + B Werkzeuge Maschinen Handels GmbH



© A + B Werkzeuge Maschinen Handels GmbH

