

HKS HKS 34 MG (1125-9111104)



Control type
konventionell

Construction year
1986

Machine no.
1125-9111104

Make
HKS

Location
Ahaus

** Machine from a vocational training center

** In good condition (!!)

Features:

- Compact design with electro-hydraulic quick clamping
- Electric height adjustment
- Automatic spindle feed
- Heavy-duty / robust machine table
- Thread cutting device
- Pole-changing motor
- Continuously variable speed adjustment
- * Including analog speed display
- Machine base
- 1x Machine vise
- Emergency stop button at the front
- Original operating instructions + machine card

Machine attributes

bore capacity in steel (diameter):	38.0 mm
bore capacity in cast iron:	45.0 mm
arm length:	415 - 1050 mm
revolutions per minute:	38 - 2000 U/min
bore spindles - Morse Taper:	4 MK
feed range:	0.05 - 0.45 mm/min
quill stroke:	170 mm
table surface area:	1200 x 560 mm
T-slots:	3 x 18 x 150
work height max.:	800 mm
Height adjustment of the drill spindle:	200 - 650 mm
threading:	M 28 / M 34
voltage:	380 V
total power requirement:	1.5 / 3.0 kW
weight of the machine ca.:	1600 kg
range L-W-H:	1200 x 1600 x 1950 mm

Machine images





© A + B Werkzeuge Maschinen Handels GmbH

HKS HKS Maschinenbau GmbH
D – 7700 Singen (Hohentwiel)

Maschinen-Type	HKS 34MG	Ventilspannung	24 V
Maschinen-Nr.	34121A	Sicherung in der Zuleitung	20 A-träge
Baujahr	1986	Leitungsquerschn. der Zuleitung	2,5 mm²
Gewicht	1600 Kg	Nennstrom	12 A
Schaltplan-Nr.	25.2.123 509.00	Anschlußwert	5 KW
Betriebsspannung	380 V 50 Hz		
Steuerspannung	220 V 50 Hz		
Lampenspannung	220 V 50 Hz		
Kupplungsspannung	24 V-		