

## KALTENBACH KKS 400 (1125-3160045)



**Control type**  
konventionell

**Construction year**  
unbekannt

**Machine no.**  
1125-3160045

**Make**  
KALTENBACH

- The powerful, 2-stage gear was specially designed for cuts in solid material designed
- The user has a total of 4 blade speeds for optimal adjustment the material available
- The large bearing rotary table with internal table clamping and Precision stops at 0/45/60° ensure quick adjustability miter cuts
- The vice with quick clamping (optional is a pneumatic one Vise = MA, available) is with screwed vise jaws Mistake. With their ribbing, these ensure optimal hold of the workpiece
- Underframe with lockable door, chip drawer and removable Coolant pan with electric coolant pump
- Chip removal brush

## Machine attributes

|                                |                       |
|--------------------------------|-----------------------|
| saw blade diameter:            | 370 mm                |
| cutting diameter:              | 115 mm                |
| stroke:                        | - mm                  |
| capacity 90 degrees: flat:     | 300 x 35 mm           |
| cutting speed:                 | 11 / 15 / 22 m/min    |
| total power requirement:       | 1,4 kW                |
| weight of the machine ca.:     | 850 kg                |
| dimensions of the machine ca.: | 1100 x 1100 x 1600 mm |

## Machine images



**SANDERS**

HEINZ

MASCHINEN  
WERKZEUGE  
SCHWEISSTECHNIK

# Maschinen


[www.heinz-sanders.de](http://www.heinz-sanders.de)**Papenburg**Heinz Sanders GmbH  
Friederikenstraße 100  
26871 Papenburg  
info@heinz-sanders.de**Niederlangen**Heinz Sanders GmbH  
Fresenburger Weg 4  
49779 Niederlangen  
maschinen@heinz-sanders.de**Spelle**Heinz Sanders GmbH  
Robert-Bosch-Straße 9  
48480 Spelle  
spelle@heinz-sanders.de

© Heinz Sanders GmbH

**KALTENBACH****Typ** KKS**Nr** 31652

|  | m/min<br>(Ø370) | Material<br>Matière                                                          |
|-----------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------|
| I                                                                                 | 11              | Stahl hart<br>Acier dur<br>Steel high tensile<br>< 120kg/mm <sup>2</sup>     |
| II                                                                                | 15              | Stahl mittelhart<br>Acier semi dur<br>Steel medium<br>< 80kg/mm <sup>2</sup> |
| III                                                                               | 22              | Stahl weich<br>Acier doux<br>Steel mild<br>< 50kg/mm <sup>2</sup>            |

|       | A                    | 1,5 l                 |
|-------|----------------------|-----------------------|
| BP    | BP ENERGOL-GR 100-EP | Ölwechsel 1/4 jährl.  |
| SHELL | SHELL Macoma Oil 37  | Oil change 1/4 yearly |
| Mobil | Mobil Compound AA    | Vidange d'huile       |
| Esso  | PEN-O-LED-EP-1       | tous les 3 mois       |

**B**Kühlmittel  
Coolant solution  
Liquide d'arrosage  
  
Wasser water  
eau  
+ 5% CUTOL 2000\*\* Zu beziehen durch unsere Firma  
Obtainable by our representative  
Livvable par notre représentantHANS KALTENBACH MASCHINENFABRIK  
LÖRRACH W.-GERMANY TEL. 8595VO  
TELEFO