

KALTENBACH KKS 400 (1125-3160045)



Control type
konventionell

Construction year
unbekannt

Machine no.
1125-3160045

Make
KALTENBACH

- The powerful, 2-stage gear was specially designed for cuts in solid material designed
- The user has a total of 4 blade speeds for optimal adjustment the material available
- The large bearing rotary table with internal table clamping and Precision stops at 0/45/60° ensure quick adjustability miter cuts
- The vice with quick clamping (optional is a pneumatic one Vise = MA, available) is with screwed vise jaws Mistake. With their ribbing, these ensure optimal hold of the workpiece
- Underframe with lockable door, chip drawer and removable Coolant pan with electric coolant pump
- Chip removal brush

Machine attributes

saw blade diameter:	370 mm
cutting diameter:	115 mm
stroke:	- mm
capacity 90 degrees: flat:	300 x 35 mm
cutting speed:	11 / 15 / 22 m/min
total power requirement:	1,4 kW
weight of the machine ca.:	850 kg
dimensions of the machine ca.:	1100 x 1100 x 1600 mm

Machine images

© Heinz Sanders GmbH




© Heinz Sanders GmbH



© Heinz Sanders GmbH



© Heinz Sanders GmbH



© Heinz Sanders GmbH




KALTENBACH

Typ KKS

Nr 31652

90°	m/min (Ø370)	Material Matière
I	11	Stahl hart Acier dur Steel high tensile < 120kg/mm ²
II	15	Stahl mittelhart Acier semi dur Steel medium < 80kg/mm ²
III	22	Stahl weich Acier doux Steel mild < 50kg/mm ²

	A	1,5 l
BP	BP ENERGOL-GR 100-EP	Ölwechsel 1/4 jährl.
SHELL	SHELL Macoma Oil 37	Oil change 1/4 yearly
Mobil	Mobil Compound AA	Vidange d'huile
Esso	PEN-O-LED-EP-1	tous les 3 mois



B
Kühlmittel Coolant solution Liquide d'arrosage
Wasser water eau
+ 5% CUTOL 2000*

* Zu beziehen durch unsere Firma
Obtainable by our representative
Livvable par notre représentant

HANS KALTENBACH MASCHINENFABRIK
LÖRRACH W.-GERMANY TEL. 8595