

MAHO MH 400 (1125-9131231)



Control type
 konventionell

Construction year
 1993

Machine no.
 1125-9131231

Make
 MAHO

Location
 48683 Ahaus

** from a training center

** very little run (!!)

** operating hours approx. 504 hours

Equipment:

- robust conv. electro-motorized universal milling machine
- HEIDENHAIN digital display incl. control panel
- * swiveling, front right
- * display font 0.005/0.001 mm
- Electro-motorized adjustment of all axes (X/Y/Z axis)
- * rapid traverse in all 3x directions
- * Manual adjustment via handwheel also possible
- Infinitely variable speed adjustment
- Vertical milling head with quill adjustment
- * ISO 40 tool holder
- * automatic tool clamping with clamping/pull bar
- * Swivel milling spindle guard
- Robust work table incl. T-slots ... 650 x 350 mm
- * Number/size of T-slots 5 pieces 14H7

* Distance T-slots 63.0 mm

* Safety housing (own construction)

- Coolant device incl. lower chip tray

- Counter support = horizontal milling device

- Halogen/machine lighting

- Central lubrication incl. container

- Original operating instructions

Machine attributes

x-travel:	400 mm
y-travel:	375 mm
z-travel:	350 mm
turning speeds:	63 - 4000 U/min
spindle taper ISO:	40
Pull studs:	ISO TYP B
quill stroke:	50.0 mm
table::	650 x 350 mm
workpiece weight:	max. 200 kg
T-slots:	5x 14H7
feed range:	10 - 1000 mm/min
rapid traverse:	1.5 / 1.0 m/min
Number of working hours:	ca. 504 h
control:	DIGI "VRZ 650"
voltage:	380 V
total power requirement:	8.0 kW
weight of the machine ca.:	1550 kg.
range L-W-H:	1640 x 1580 x 1840 mm

Machine images





