Papenburg
Heinz Sanders GmbH
Friederikenstraße 100
26871 Papenburg
info@heinz-sanders.de

Niederlangen
Heinz Sanders GmbH
Fresenburger Weg 4
49779 Niederlangen
maschinen@heinz-sanders.de

Spelle
Heinz Sanders GmbH
Robert-Bosch-Straße 9
48480 Spelle
spelle@heinz-sanders.de

PEDDINGHAUS HYDRAULIC 280 (1125-8412009)

Control type
konventionell

Machine no.
1125-8412009

Make
PEDDINGHAUS

Location
manufacturer factory

Furnishing:

- Punch quick-change device up to Ø 31 mm - green series -
  installed: round punch no. 5 Ø 25.0 mm and round die no. 3 Ø 25.7 mm
- Free: LED lighting in the punching area
- Swiveling scraper (plates exchangeable)
- Various material support tables are available separately
- Brace
- 2-step foot switch, with double press for grain search function
- electrical controls
- Stroke length and stroke position continuously adjustable
- integrated hydraulic unit with oil filling
- Performance specifications apply to a material strength of 450 N/mm²
- Main connection cable and plug for 16 amps are not included in the scope of delivery

Machine attributes

punching pressure:	28.0 t
punching cross-cut in cmm:	31 in 7.0 mm ST
throat:	250 mm
dayligth:	223 mm
no. of strokes:	10 - 30 Hub/min
oil volume:	32.0 ltr.
work height max.:	1033 mm
total power requirement:	3.0 kW
weight of the machine ca.:	553 kg
dimensions of the machine ca.:	730 x 540 x 1530 m

Machine images