

PEDDINGHAUS Peddicat 500 (1125-3410029)



Control type
konventionell

Construction year
2005

Machine no.
1125-3410029

Make
PEDDINGHAUS

Location
D - 49779 Niederlangen

Features:

- Flat steel shears

Cuts flat steel: up to 350 x 13 mm

L-steel, 45° cut: up to 100 x 8 mm

Blade cutting length: 370 mm

Working height: 734 mm

- Profile and bar steel shears

Shear cross-section: max. 1550 mm²

Stroke, infinitely adjustable: 10 - 36 mm

- Shears with standard blade 90°

L-steel 90° cut: up to 100 x 8 mm

Round steel: 32 + 17 mm

Square steel: 30 x 18 mm

U-steel, 90° cut: up to 100 mm

Double-T steel, 90° cut: up to 100 mm

Working height (center of blade cross): 1044 mm

- Notcher with square notcher

U-steel, in flange: 80 - 120 mm

Double-T steel, in flange 80 - 120 mm

Notch width: 44.5 mm

Notch depth: 50.0 mm

Working height: 1000 mm

Machine attributes

round bar steel:	32 / 17 mm
square edge steel:	30 x 18 mm
L-beam:	100 x 8 mm
punching pressure:	50 t
weight of the machine ca.:	900 kg
dimensions of the machine ca.:	1000 x 700 x 1700 mm

Machine images



