

# Maschinen www.heinz-sanders.de

Papenburg Heinz Sanders GmbH Friederikenstraße 100 26871 Papenburg info@heinz-sanders.de

Niederlangen Heinz Sanders GmbH Fresenburger Weg 4 49779 Niederlangen maschinen@heinz-sanders.de **Spelle**Heinz Sanders GmbH
Robert-Bosch-Straße 9
48480 Spelle
spelle@heinz-sanders.de

## **SANDERS HGK-5 (1125-8458504)**



Control type konventionell

Machine no. 1125-8458504

Make SANDERS

**Location** 48683 Ahaus

#### Stable turning

The HGK\_Series has two synchronously working drive units that are used for ensure continuous rotation with stepless speed control. Of the Roller spacing can be increased and decreased manually using locking pins to achieve a large diameter range of the workpieces.

### Characteristics:

- For rotating and positioning
- in the field of machine, container, plant and pipeline construction
- Two synchronously running drive motors
- Adjustable rotation speed.
- PU castors
- Adjustment is via bolts
- Remote control

### Scope of delivery:

- 1x controller
- 1x driven unit
- 1x traveling unit

## **Machine attributes**

weight max.:5000 kgtable turning speeds:6.0 - 60.0 m/hroll diameter:250 mmWheel width:120 mmworkpiece diameter:250 - 2800 mmtotal power requirement:0.75 kWweight:ca. 300 kg

range L-W-H: ca. 4165 x 1360 x 1200 mm

## **Machine images**