Papenburg
Heinz Sanders GmbH
Friederikenstraße 100
26871 Papenburg
info@heinz-sanders.de

Niederlangen
Heinz Sanders GmbH
Fresenburger Weg 4
49779 Niederlangen
maschinen@heinz-sanders.de

Spelle
Heinz Sanders GmbH
Robert-Bosch-Straße 9
48480 Spelle
spelle@heinz-sanders.de

UNICRAFT PG-E 60 SEA (1125-6706060)

® Heinz Sanders GmbH



Control type
konventionell

Construction year
NEU

Machine no.
1125-6706060

Make
UNICRAFT

Location
49779 Niederlangen

Synchronous power generator PG-E 60 SEA / 6706060
Drive SC188F
Power factor 1.0 cos
Starter manual start / electric start
Fuel: Gas
Capacity tank 25 l
Sound pressure level Lp 76 dB(A)
Sound power level Lw 97 dB(A)
Type synchronous
Nominal voltage 230 V
Apparent power at LTP 5.5 kVA
Active power at LTP 5.5 kW
Apparent power at COP 5.0 kVA
Active power at COP 5.0 kW
Protection class generator IP 23
Socket design 2 x 230 V, Schuko / 1 x 230 V, 32 A
Protection class sockets IP 44

* All alternators with copper windings

* Short-term power up to 3 times the rated power
* Automatic voltage regulation AVR provides constant output voltage and enables the operation of sensitive devices
* Overload protection by thermal circuit breaker
* Low oil shutdown with warning lamp
* 3 in 1 display for voltage, frequency and operating hours
* Long running time due to large tank
* Tank with level indicator
* Connections ergonomically favorable at the front
* Easy transport thanks to the wheel set and stable folding handles

Machine attributes

rated capacity:	5,5 kVA
capacity in kVA:	5,0 kVA
Heating capacity:	--
power fuel:	Benzin
weight of the machine ca.:	90,5 kg
dimensions of the machine ca.:	700x526x580 mm

Machine images