

# Maschinen www.heinz-sanders.de

Papenburg
Heinz Sanders GmbH
Friederikenstraße 100
26871 Papenburg
info@heinz-sanders.de

Niederlangen Heinz Sanders GmbH Fresenburger Weg 4 49779 Niederlangen maschinen@heinz-sanders.de

Heinz Sanders GmbH Robert-Bosch-Straße 9 48480 Spelle spelle@heinz-sanders.de

## **UNICRAFT SSK 3.1 (1125-3500080)**



Control type konventionell

Construction year 2015

Machine no. 1125-3500080

Make UNICRAFT

**Location** 49779 Niederlangen

#### Description

- Suitable for various blasting materials, e.g., quartz, glass beads, plastic beads, etc.
- Ideal for cleaning, derusting, or paint removal from all types of metal parts, e.g., engine parts, fittings, signs, housings, rims, hinges
- High-quality latex work gloves are firmly attached to the housing
- Optimal visibility and occupational safety during workpiece processing thanks to the viewing window with adhesive protective film
- Dust-free working thanks to circumferential seals on the lid and door frame
- Sturdy storage grid allows workpieces to be placed inside the cabin
- With drain opening for changing the blasting material
- Suction pipe for the blasting material attached to the bottom of the collection container
- With compressed air connection on the outside
- Glass bead blasting material, corundum blasting material, silicon carbide, plastic blasting material, etc. can be used

#### Equipment details:

- Very large front flap opening upwards with gas pressure springs for quick and easy loading and unloading

- Integrated extraction system with replaceable air filter
- Blasting gun without finger trigger ? air flow controlled via foot pedal
- Two fluorescent tubes (230 volts) in separate housing with protective screen and replaceable protective film, including five replacement films
- Light switch with dual function: extraction and cabin lighting are switched on and off simultaneously
- Working pressure regulated via pressure regulator with pressure gauge

### **Machine attributes**

through-put width: 580 mm working heigth: 580 mm

air consumption:

400 - 800 I/min

working pressure:

3,4 - 8,0 bar

suction capacity:

17,4 m³/h

total power requirement:

1,2 kW

weight of the machine ca.:

115 kg

dimensions of the machine ca.: 1225 x 935 x 1640 mm

## **Machine images**

® Heinz Sanders GmbH



